



An Electronic Transaction Company

Point-of-Sale

**Equipment
Supplies
Accessories
Repairs**

Customer Support

713-629-0906

Hours:

7:00 am to 7:00 pm

M-F



Bancnet Technical Support Services

www.banc.net

Open 24 Hours

Scroll Down or click on thumbnails to
view Brochure or User Guide pages

T77 Terminal

Integrated Terminal with High Performance Printer from Hypercom®

The T77 is a compact, high-performance terminal that achieves its attractive price through the innovative use of technology. The T77 terminal supports draft capture, debit, check and proprietary card processing as well as new payment vehicles such as chip card-based credit/debit cards and stored value cards. Combined with the high-speed, easily replaceable printer module, the T77 is perfect for a wide range of applications.

Product Highlights:

- ✓ Printer available in 3 options: Thermal, Sprocket or Friction
- ✓ User-friendly
- ✓ Small footprint
- ✓ 35 Key keyboard is easy to learn; simple to use
- ✓ Under 10 second dial transaction response time
- ✓ Easy to change paper and ribbons
- ✓ Cashier replaceable printer module
- ✓ High visibility 2 x 20 back-lit LCD display
- ✓ Full track 1 and 2 card reader is standard
- ✓ IC card reader option
- ✓ Backwards software compatibility with "T7E" and "T7P" terminals



In all applications, the T77 saves on clerk training, installation time and telephone costs, processing and settlement time. Its integrated printer reduces footprint. Its easily removable printer module greatly reduces printer maintenance and can be changed by the cashier. The wide range of telecommunications, display, keypad, card reader and system connectivity options meets the needs of the ever-changing demands of today's marketplace.



T77-S
Sprocket Printer



The Global Leader in Electronic Transaction Solutions™

1-877-Hypercom

2851 W. Kathleen Road, Phoenix, AZ 85053
Tel: (602) 504-5000 • Fax: (602) 504-4578

Specifications

Protocol	SDLC (Synchronous) and Asynchronous (VISA 1 & 2)
Display	2 x 20 back-lit LCD
Options	64 x 128 graphics display
Keyboard	35 keys
Options	41 keys with graphics display; 59 keys with QWERTY Keyboard
Memory	
EPROM	32k
RAM	256k
Options	512k, 1 Mb
Card Reader	Tracks 1 & 2 simultaneous read
Options	Track 3 and JIS II reader
Communications	LAN, RS485, RS422, RS232
Options	Additional RS232 port
Modem	1200 or 2400 baud
Power	+24 Vdc, 200mA (1A while printing)
Peripheral Compatibility	S7C, S7SC, S8, ICE
Dimensions	9 1/4" W x 6 3/4" D x 4 1/4" H
Weight	3.65 lbs.
Memory/Clock Back-up	Lithium Battery (5 years)
Operating Temperature	0°C to +45°C (+32°F to +113°F)
Relative Humidity	15-85 percent, noncondensing
ESD Resistance	12,000 volts
Options	AMPS Cellular Radio CDPD Radio IC Card Reader, ISO 7816 Secure Application Module (SAM) 9600 baud modem External Keyboard
Reliability	
Key Life	450,000 operations
Card Reader	900,000 MTBF
IC Card	450,000 operations
Warranty	5 Year Terminal Warranty

Printer	T77-F	T77-S	T77-T
Method	Impact Line	Impact Line	Thermal
Columns	40	23	48
Font	7 x 7 impact dot matrix	5 x 7 impact dot matrix	Scalable
Paper	3.0"	3.0"	80mm
	76.2 (3.0")	76.2 (3.0")	80mm (3.15")
	1, 2, or 3-ply carbonless	1, 2, or 3-ply carbonless	multiple print Thermal
Print Direction	Bi-directional	Bi-directional	N/A
Print Speed	3.1 lines per second	4 lines per second	12 lines per second
Character size (w/h)	1.59mm/2.87mm	1.59mm/2.87mm	scalable
Ribbon	RC 2001B	RC 2001B	N/A
Ribbon Size	13mm	13mm	N/A
Head Life	2,000,000 lines	2,000,000 lines	5,000,000 lines



Replaceable printer module



Corporate Office

2851 West Kathleen Rd. • Phoenix, Arizona 85053
Tel: (602) 504-5000 • Fax: (602) 504-4578

International Regional Offices

Hypercom Asia / Pacific Rim
Kowloon Bay, Hong Kong
Tel: 852-2561-6800
Fax: 852-2561-5890

Hypercom EMEA
Surrey, England
Tel: 44-1483-718600
Fax: 44-1483-718601

Hypercom Latino America
Miami, Florida
Tel: 305-477-0315
Fax: 305-477-4172

Regional Sales Offices

Atlanta, GA
Tel: 770-641-7117
Fax: 770-645-4490

Chicago, IL
Tel: 708-301-6820
Fax: 708-301-6841

Los Angeles, CA
Tel: 310-455-0708
Fax: 310-455-2969

New York, NY
Tel: 516-676-5779
Fax: 516-676-5806