

BANC

NET

An Electronic Transaction Company

Point-of-Sale

**Equipment
Supplies
Accessories
Repairs**

Customer Support

713-629-0906

Hours:

7:00 am to 7:00 pm

M-F



Bancnet Technical Support Services

www.banc.net

Open 24 Hours

Scroll Down or click on thumbnails to
view Brochure or User Guide pages

T7P

integrated POS terminal with printer

Get efficient upgrading of authorization-only equipment:

- *Takes up less counterspace with small footprint*
- *Trains cashiers with easy-to-learn, simple-to-use 35-key keyboard*
- *Delivers fast transactions and authorizations*
- *Changes paper, ribbons and printer module easily and quickly*
- *Smart card reader option, EMV-certified*



Ideal for Upgrades

The T7P is designed for upgrading authorization-only equipment and for merchants moving to data capture and debit applications. It features an integrated modular impact or quiet thermal printer.

Reads All Card Formats

The T7P can read all types of credit, debit, check and charge cards and an external PIN pad can be attached for supporting cardholder entry of PIN numbers. Dedicated function keys allow one-step operation of everyday processes.

Additional Benefits

Price/performance benefits of the T7P include savings on user training, reduced telephone line costs and shorter processing and settlement times. The T7P also accommodates new software applications demanded by the marketplace which can be remotely downloaded from a sophisticated Terminal Management System.

Hypercom T7 Terminals. Focused on excellence.

For more information about the T7P, please visit www.hypercom.com

innovation. results. leadership.



T7P Specifications

integrated POS terminal with printer

Display	LCD Backlight	2 lines x 20 characters 25,000 hours (calculated)															
Card reader	Magnetic stripe Reliability	Tracks 1, 2 standard; Track 3 optional 400,000 reads (calculated)															
Card option	IC card interface	ISO 7816, EMV-certified															
Keypad	Silicone rubber Reliability	35 keys 350,000 operations (calculated)															
Comms	Modem LAN PIN pad port Peripheral	2400 or 1200 bps; synchronous (SDLC) & asynchronous; 9600 bps optional RS485 Hypercom LAN 2-wire or 4-wire, RS422 S7C, S7SC, S8, P7E, ICE, HFT 105															
Printer		<table><thead><tr><th></th><th><u>Thermal</u></th><th><u>Friction</u></th></tr></thead><tbody><tr><td>Columns</td><td>40</td><td>40</td></tr><tr><td>Paper width</td><td>2.26 in/57.5 mm</td><td>2.26 in/57.5 mm</td></tr><tr><td>Paper type</td><td>Single-ply</td><td>1, 2 or 3-ply</td></tr><tr><td>Reliability</td><td>5 million lines (calc.)</td><td>1.35 million lines (calc.)</td></tr></tbody></table>		<u>Thermal</u>	<u>Friction</u>	Columns	40	40	Paper width	2.26 in/57.5 mm	2.26 in/57.5 mm	Paper type	Single-ply	1, 2 or 3-ply	Reliability	5 million lines (calc.)	1.35 million lines (calc.)
	<u>Thermal</u>	<u>Friction</u>															
Columns	40	40															
Paper width	2.26 in/57.5 mm	2.26 in/57.5 mm															
Paper type	Single-ply	1, 2 or 3-ply															
Reliability	5 million lines (calc.)	1.35 million lines (calc.)															
Memory	RAM EPROM RAM backup	Up to 1.0 MB 32 KB 5-year battery															
Power	AC DC	85-250V, 50/60 Hz 24V, 1A															
Environment	Temperature Humidity ESD	0-45 C/32-110 F Max 85%, non-condensing 12,000 volts															
Footprint	Dimensions	6.25 in x 11.5 in x 4.5 in / 15.88 cm x 29.21 cm x 11.43 cm															
Weight	Approximate	1.98 lbs/0.74 kg															
Product lifecycle	Reliability	100,000 hours (calculated), not including printer															

Specifications subject to change without notice.

World Headquarters/ North America

Hypercom Corporation
2851 W. Kathleen Road
Phoenix, Arizona 85053
USA
Tel: +1.602.504.5000
Fax: +1.602.504.4578

Latin America

Hypercom Latino America
Rua Joaquim Floriano 72
16° andar Cj161
04534-000 ItaimBibi
São Paulo, Brazil
Tel: +55.11.3365.2600
Fax: +55.11.3365.2610

Asia/Pacific Rim

Hypercom Asia Ltd.
21/F Metro Centre II
21 Lam Hing Street
Kowloon Bay, Kowloon
Hong Kong
Tel: +85.2.2561.6800
Fax: +85.2.2561.5890

Europe/Middle East/Africa

Hypercom EMEA, Inc.
Unit 2, Woking Eight
Forsyth Road
Woking, GU21 5SB,
United Kingdom
Tel: +44.1483.718600
Fax: +44.1483.718601

©2002 Hypercom Corporation, all rights reserved. Hypercom, the Hypercom logo, ePOS-incommerce, FastPOS, HyperWare, ICE-PAC and Term-Master are registered trademarks of Hypercom Corporation. BioPIN, ePicReceipts, FastCOM, HyperPASS, HyperSafe, ICE and SureSign are trademarks of Hypercom Corporation. All other products or services mentioned in this document are trademarks, service marks, registered trademarks or registered service marks of their respective owners.

Hypercom Corporation (NYSE: HVC) is the leading global provider of electronic payment solutions that add value at the point-of-sale for consumers, merchants and acquirers, and yield increased profitability for its customers. Hypercom products include secure, Web-enabled card payment terminals that work seamlessly with its networking equipment and software applications for e-commerce, m-commerce, smart cards and traditional payment applications. The company's widely-accepted ePOS-incommerce (epic) framework of consumer-activated, EMV-certified, touch-screen ICE (Interactive Consumer Environment) terminals enable acquirers and merchants to decrease costs, increase revenues and improve customer retention. Headquartered in Phoenix, Arizona, USA, Hypercom is independently acknowledged as the leading provider of point-of-sale card payment terminals worldwide. Demand for Hypercom terminals surpassed one million units last year alone. Hypercom today maintains an installed base of more than 5 million card payment terminals in over 100 countries that conduct more than 10 billion transactions annually.