



An Electronic Transaction Company



Point-of-Sale

**Equipment
Supplies
Accessories
Repairs**

Customer Support

713-629-0906

Hours:

7:00 am to 7:00 pm

M-F



Bancnet Technical Support Services

[www. banc. net](http://www.banc.net)

Open 24 Hours

Scroll Down or click on thumbnails to
view Brochure or User Guide pages

T7P Terminal

Integrated Terminal and Printer from Hypercom

The T7P, with its integrated, modular printer, and the ability to support draft capture, debit, check and proprietary card processing, is the right choice for your POS product needs, for upgrading existing auth-only equipment, or for merchants moving to debit. Whatever your selection criteria, the T7P is a clear winner.

Product Highlights:

- ✓ Small footprint
- ✓ 35 Key keyboard is easy to learn; simple to use
- ✓ 256K memory
- ✓ Under 10 second dial transaction response times
- ✓ Clerk-friendly operations make it easy to change paper and ribbons
- ✓ Cashier replaceable printer module
- ✓ High visibility 2x20 back-lit LCD display
- ✓ Full track 1 and 2 card reader is standard
- ✓ IC card reader option



Regardless of your POS application, the T7P is a winner when it comes to price-performance. You'll save on clerk training, telephone line costs, processing time, and settlement time; at the right price and with room in the T7P to accommodate new software functionality as it is demanded by the marketplace.

The unique replaceable printer module of the T7P eliminates any reliability problems.



T7P shown in retail situation



**The Global Leader in Electronic
Transaction Solutions™**

1-877-HYPERCOM

2851 W. Kathleen Road, Phoenix, AZ 85053
Tel: (602) 504-5000 • Fax: (602) 504-4578
www.hypercom.com

T7P

Specifications

Protocol	SDLC (Synchronous) and Asynchronous (VISA 1 & 2)
Display	2 x 20 Back-lit LCD
Keyboard	35 keys
Memory	
EPROM	32k
RAM	512k
Optional	1 Mb
Card Reader	Tracks 1 & 2 simultaneous read (Track 3 optional)
IC Card Reader	ISO 8316, EMV compatible (optional)
Communications	LAN, RS485, 2 wire or 4 wire
Modem	1200 or 2400 baud
Power	+24 Vdc, 200mA
Auxiliary Ports	PINPad RS422/RS485
Peripheral Compatibility	S7C, S7SC, S8, P7E, ICE
Dimensions	6 1/4" W x 11 1/2" D x 4 1/2" H (with full 3" diam. roll of paper)
Weight	1.98 lbs.(2.40 lbs. with full 3" paper roll)
Memory/Clock Back-up	Lithium Battery (5 years)
Operating Temperature	0PC to +45PC (+32PF to +113PF)
Relative Humidity	15-85 percent, noncondensing
ESD Resistance	12,000 volts
Options	Memory upgrades to 1 Mb Track 3 reader Graphics Display (64 x 128) QWERTY Keyboard IC Card Reader RS232 port 9600 baud modem AMPS CELLULAR CDPD CELLULAR
Reliability	
Key Life	350,000 Operations
Card Reader	400,000 reads
Warranty	5 Year Terminal Warranty

Printer

	T7P-F	T7P-T
Method	Epson 192	Epson MT 101
Columns	Impact line	Thermal line
Font	40	40 (42) 100% font
Paper	OS Hardware	OS Hardware
Print Speed	5 x 7	Scalable
Line Pitch	57.5mm 2 ply carbonless	57.5mm thermal
Character size (w/h)	Mitsubishi Paper N40	Nippon Paper TF50KS-E
Ribbon	1, 2, or 3-ply carbonless	Single ply
Head Life	1.5 lines per second	7 lines per second
	3.7mm	3.38mm
	1.1mm/2.6mm w/h	0.875mm/2.62mm w/h
	ERC-09 ERC-22	N/A
	1,350,000 lines	5,000,000 lines



Corporate Office

2851 West Kathleen Rd. • Phoenix, Arizona 85053
Tel: (602) 504-5000 • Fax: (602) 504-4578

International Offices

Hypercom ASIA/Pacific Rim
Kowloon, Hong Kong
Tel: 852-2561-6800
Fax: 852-2561-5890

Hypercom, EMEA
Surrey, England
Tel: 44-1483-718600
Fax: 44-1483-718601

Hypercom Latino America
Miami, Florida
Tel: (305) 477-0315
Fax: (305) 477-4172

Regional Sales Offices

Atlanta, GA
Tel: (770) 641-7117
Fax: (770) 645-4490

Chicago, IL
Tel: (708) 301-6820
Fax: (708) 301-6841

Los Angeles, CA
Tel: (310) 455-0708
Fax: (310) 455-2969

New York, NY
Tel: (516) 676-5779
Fax: (516) 676-5806